



Washer extractors

High Spin washer extractors TP

HIGH SPIN WASHER EXTRACTOR, LA-120 TP S

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	1.836,00	1.900,00
Depth	mm	1.863,00	1.940,00
Height	mm	2.245,00	2.290,00
Weigth	Kg	3.300,00	3.500,00
Volumen	m3		8,44
<u>ELECTRICITY</u>			
<u>Electric power</u>			15,00
230V -1+N			NO
230V - III		OPC3x10+T-63A	
400V - III+N		4x4+T-32A	
<u>WATER</u>			
Water consumption (lit/h)			1.300,00
Pressure (Kg/cm2)			2 - 4
<u>GAS</u>			
Not used			
<u>STEAM</u>			
Consumption	kg/h		300,00
Pressure	bar		4-8
<u>AIR</u>			
Not used			
<u>LEVEL SOUND</u>			
	(dB)		70,00

HIGH SPIN WASHER EXTRACTOR, LA-120 TP S

Made of stainless steel.
 Capacity: 133 kg (1:9) or 120 kg (1:10).
 Microprocessor "Touch Plus Control" with display.
 26 pre-set programs (4 economic programs).
 Possibility of programming, export and import programs through USB memory, without limite.
 "WASH CONTROL" management software included.
 Digital sequence display.
 8 signals for automatic liquid dosing, programmable in time and delay.
 Possibility to install an automatic detergent doser on the rear of the machine.
 Detergent dispenser with 5 compartments (pre-wash, wash, bleachers and softeners).
 Water levels completely modifiable.
 3 water inlets (Hot water, Cold water, Soft water).
WET CLEANING SYSTEM:
 -Water levels completely modifiable.
 -Possible manual dosing for evey 8 signals during the cycle.
 -Minimum washing speed: 15 r.p.m.
 -Minimum thrythm ON-OFF: 1 second.
 Safety door system.
 Drum diameter: 1.360 mm.
 Deepth drum: 840 mm.
 Door diameter: 700 mm.
 Spin speed: 680 r.p.m.
 G Factor: 350.
 These machines have electronic control of imbalance with frequency variator, that detects the load uncentered before spinning.
 Wash and spin speeds are configurable.
 No need to anchorage to the floor.
 Second drain option.
 Easy to attach automatic doser dispenser at rear of machine.
 Water consumption in program n° 2 60°: 1.300 litres.
 Heating by steam produced in an external generator.
 Inlet pressure: 4 bar.
 Total power: 15 kW.
 Dimensions: 1.836 x 1.863 x 2.245 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	1.400	0	2.250		0
DRAIN	1.100	0	350	4"	
DRAIN	700	0	350	4"	
COLD WATER	730	0	2.105	1-1/2"	
SOFT COLD WATER	450	0	2.105	1-1/2"	
HOT WATER	590	0	2.105	1-1/2"	
STEAM Inlet	1.195	0	2.105	1-1/4"	

