



### Tumble Dryers

#### Tumble Dryers Economic Line

## TUMBLE DRYER, SC-35 E ECONOMIC LINE

### DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	<b>985,00</b>	<b>1.090,00</b>
Depth	mm	<b>1.210,00</b>	<b>1.350,00</b>
Height	mm	<b>1.946,00</b>	<b>2.105,00</b>
Weigth	Kg	<b>350,00</b>	<b>390,00</b>
Volumen	m3		<b>3,10</b>

### ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		<b>NO</b>
230V - III		<b>3x70+T - 180 A</b>
400V - III+N		<b>4x25+T - 125 A</b>

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### LEVEL SOUND

(dB) **66,00**

### TUMBLE DRYER, SC-35 E ECONOMIC LINE

Load Capacity : 37 kg. (load factor 1:18) or 30 kg (load factor 1:22).

Production: + 66 kg/h.

Galvanized steel body.

Axial airflow.

Time selector.

Temperature selector.

COOL DOWN at end of cycle.

Lamp indicator ON and HEATING.

Open door with safety device.

EMERGENCY stop button.

Frecuency speed variator.

Alarm noise indicator at end of cycle.

Air extraction volume: 1500 m3/h.

Drum in galvanized steel.

IMPORTANT: Reversing drum.

Drum diameter: 947 mm

Depth of drum: 936 mm

Diameter of door: 802 mm.

Fluff filter in lower part .

Transmission by means of pulleys.

Main heating system: electric.

Electrical connection : 400 V - III+N+ GROUND - 50/60 Hz.

Heating power: 36 kW

Total power: 37,15 kW.

Dimensions: 985 x 1.210 x 1.946 mm

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	205	0	1.490		
EXHAUST	744	0	167	200 mm.	

