



### Tumble Dryers

#### Tumble Dryers Green Evolution Plus

## TUMBLE DRYER, SR-11 MP E PLUS

### DIMENSIONS

		Article	Packed
Length	mm	785,00	880,00
Depth	mm	840,00	955,00
Height	mm	1.694,00	1.840,00
Weigth	Kg	170,00	200,00
Volumen	m3		1,55

### ELECTRICITY

Electric power	KW	
230V -1+N		NO
230V - III		3x6+T - 50 A
400V - III+N		4x4+T - 25 A

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### LEVEL SOUND

(dB) 64,00

### TUMBLE DRYER, SR-11 MP E PLUS

#### GREEN EVOLUTION PLUS series dryer.

Load Capacity : 12 kg. (load factor 1:18) or 10 kg (load factor 1:22).

Production: + 27 kg/h.

External case made of skin plate, grey color, with stainless steel aesthetics.

Axial-radial airflow gives low energy consumption and a bigger drying efficiency.

Electronic microprocessor, with 10 preset programs and programmable by means of key.

LCD display of temperature and drying time.

Programmable time and temperature.

Green Flow System, recirculation system that reintroduces the expelled hot air inside the drum.

Humidity sensor with intelligent drying, Idry SYSTEM.

Door with double glass.

COOL DOWN at end of cycle.

Push -Pull button to START/STOP.

Lamp indicator ON and HEATING.

Open door with safety device.

EMERGENCY stop button.

Frecuency speed variator.

Alarm noise indicator at end of cycle.

Air extraction volume: 870 m3/h.

IMPORTANT: Stainless steel drum.

IMPORTANT: Reversing drum .

Drum diameter: 750 mm

Depth of drum: 475 mm

Drum volume: 210 litres.

Diameter of door: 574 mm.

Reversible door hanging.

Microprocessor with diagnostic of mishaps, statistics of cycles...

Fluff filter in lower part. Indicator of dirt in the filter.

Transmission by means of motoreducer .

Main heating system: electric

Electrical connection : 400 V - III+N- 50/60 Hz.

Heating power: 12 kW

Total power: 12,55 kW.

Dimensions: 785 x 840 x 1.694 mm

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	528	0	821		0
EXHAUST	558	0	169	200 mm.	

