



Tumble Dryers

Tumble Dryers High Efficiency

TUMBLE DRYER, SR-11 MP HE

DIMENSIONS

		Article	Packed
Length	mm	785,00	880,00
Depth	mm	1.090,00	1.200,00
Height	mm	1.694,00	1.840,00
Weigth	Kg	170,00	200,00
Volumen	m3		1,55

ELECTRICITY

Electric power	KW	
230V -1+N		NO
230V - III		3x2,5+T - 16 A
400V - III+N		4x1,5+T - 10 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 64,00

TUMBLE DRYER, SR-11 MP HE GREEN EVOLUTION

Fagor presents their "High Efficiency" tumble dryers with the greatest energy savings. These new Heat Pump tumble dryers with low consumption represent a revolution as they offer around a 60% of energy saving.

These machines do not require extraction, and their technology makes them also ideal to be installed in places without access to the exterior of the building.

Load Capacity : 12 kg. (load factor 1:18) or 11 kg (load factor 1:22).

Production: ± 12 kg/h.

External case made of skin plate, grey color, with stainless steel aesthetics.

Axial-radial airflow gives low energy consumption and a bigger drying efficiency.

Electronic microprocessor, with 10 preset programs and programmable by means of key.

LCD display of temperature and drying time.

Programmable time and temperature.

COOL DOWN at end of cycle.

Push -Pull button to START/STOP.

Lamp indicator ON and HEATING.

Open door with safety device.

EMERGENCY stop button.

Frecuency speed variator.

Alarm noise indicator at end of cycle.

IMPORTANT: Stainless steel drum.

IMPORTANT: Reversing drum .

Drum volume: 210 litres.

Diameter of door: 574 mm.

reversible door hanging.

Microprocessor with diagnostic of mishaps, statistics of cycles...

Indicator of dirt in the filter.

Fluff filter in lower part .

Transmission by gear motor.

Electrical connection : 400 V - III+N- 50/60 Hz.

Compressor: 3,80 kW.

Motor: 0,25 kW.

Fan: 0,55 kW.

Total power: 4,60 kW.

Dimensions: 785 x 1.090 x 1.694 mm

OPTIONS:

- Humidity sensor with intelligent drying
- Door with double glass
- External case in stainless steel
- Front panel in stainless steel

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	528	0	821		0
EXHAUST	558	0	169	200 mm.	

