



Tumble Dryers

Tumble Dryers Green Evolution

TUMBLE DRYER, SR-23 MP E

DIMENSIONS

		Article	Packed
Length	mm	890,00	960,00
Depth	mm	1.345,00	1.430,00
Height	mm	1.812,00	1.930,00
Weigth	Kg	338,00	370,00
Volumen	m3		2,64

ELECTRICITY

Electric power	KW	
230V -1+N		NO
230V - III		3x25+T-125 A
400V - III+N		4x10+T - 63 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 64,00

TUMBLE DRYER, SR-23 MP E GREEN EVOLUTION

Load Capacity : 25 kg. (load factor 1:18) and 21 kg (load factor 1:22).
Production: + 46 kg/h.

External case made of skin plate, grey color, with stainless steel aesthetics.
Axial-radial airflow gives low energy consumption and a bigger drying efficiency.

Electronic microprocessor, with 10 preset programs and programmable by means of key.

LCD display of temperature and drying time.

Programmable time and temperature.

COOL DOWN at end of cycle.

Push -Pull button to START/STOP.

Lamp indicator ON and HEATING.

Open door with safety device.

EMERGENCY stop button.

Frecuency speed variator.

Alarm noise indicator at end of cycle.

Air extraction volume: 1500 m3/h.

IMPORTANT: Stainless steel drum.

IMPORTANT: Reversing drum .

Drum diameter: 855 mm

Depth of drum: 905 mm

Diameter of door: 574 mm.

reversible door hanging.

Microprocessor with diagnostic of mishaps, statistics of cycles...

Indicator of dirt in the filter.

Fluff filter in lower part .

Transmission by means of motoreducer .

Main heating system: electric

Electrical connection : 400 V - III+N- 50/60 Hz.

Heating power: 24 kW

Total power: 24,67 kW.

Dimensions: 890 x 1.245 x 1.812 mm

OPTIONS:

- Humidity sensor with intelligent drying
- Door with double glass
- External case in stainless steel
- Front panel in stainless steel
- Marine version for ships (440 V III)

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	637	0	861		0
EXHAUST	663	0	174	200 mm.	

