



### Washer extractors

#### High Spin washer extractors TP

## HIGH SPIN WASHER EXTRACTOR, LA-35 TP E

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	<b>1.095,00</b>	<b>1.165,00</b>
Depth	mm	<b>1.184,00</b>	<b>1.230,00</b>
Height	mm	<b>1.598,00</b>	<b>1.920,00</b>
Weigth	Kg	<b>750,00</b>	<b>820,00</b>
Volumen	m3		<b>2,75</b>
<u>ELECTRICITY</u>			
<u>Electric power</u>			<b>22,00</b>
230V -1+N			<b>NO</b>
230V - III		<b>3x10+T -48 A</b>	
400V - III+N		<b>4x4+T-32A</b>	
<u>WATER</u>			
Water consumption (lit/h)			<b>400,00</b>
Pressure (Kg/cm2)			<b>2 - 4</b>
<u>GAS</u>			
Not used			
<u>STEAM</u>			
Not used			
<u>AIR</u>			
Not used			
<u>LEVEL SOUND</u>			
	(dB)		<b>60,00</b>

### HIGH SPIN WASHER EXTRACTOR, LA-35 TP E

Made of stainless steel.  
 Capacity: 39 kg (1:9) or 35 kg (1:10).  
 Microprocessor "Touch Plus Control" with display.  
 26 pre-set programs (4 economic programs).  
 Possibility of programming, export and import programs through USB memory, without limite.  
 "WASH CONTROL" management software included.  
 Digital sequence display.  
 8 signals for automatic liquid dosing, programmable in time and delay.  
 Possibility to install an automatic detergent doser on the rear of the machine.  
 Detergent dispenser with 4 compartments (pre-wash, wash, bleachers and softeners).  
 Water levels completely modifiable.  
 3 water inlets (Hot water, Cold water, Soft water).  
**WET CLEANING SYSTEM:**  
 -Water levels completely modifiable.  
 -Possible manual dosing for evey 8 signals during the cycle.  
 -Minimum washing speed: 15 r.p.m.  
 -Minimum thrythm ON-OFF: 1 second.  
 Safety switch for door opening.  
 Wash and spin speeds are configurable.  
 These machines have electronic control of imbalance with frequency variator, that detects the load uncentered before spinning.  
 No need to be fixed to the floor.  
 Drum diameter: 860 mm.  
 Deepth drum: 602 mm.  
 Door diameter: 560 mm.  
 Spin speed: 975 r.p.m.  
 G Factor: 450.  
 Easy to attach automatic dosser dispenser at rear of machine.  
 Water consumption in program n° 2 60°: 400 litres.  
 Heating system: Electric.  
 Elements heating power: 21 kW.  
 Total power: 22 kW.  
 Dimensions: 1.095 x 1.184 x 1.598 mm

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	109	0	1.129		0
DRAIN	347	0	155	3"	
SOFT COLD WATER	621	0	1.509	3/4"	
COLD WATER	1.021	0	1.509	3/4"	
HOT WATER	701	0	1.509	3/4"	

