



Washer extractors

Normal Spin washer extractors TP

NORMAL SPIN WASHER EXTRACTOR, LN-35 TP E

DIMENSIONS

		Article	Packed
Length	mm	979,00	1.050,00
Depth	mm	1.066,00	1.250,00
Height	mm	1.408,00	1.600,00
Weigth	Kg	473,00	503,00
Volumen	m3		2,10

ELECTRICITY

Electric power	KW	
230V -1+N		NO
230V - III		OPC3x16+T-80 A
400V - III+N		4x6+T - 50 A

WATER

Water consumption (lit/h)	400,00
Pressure (Kg/cm2)	2 - 4

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 60,00

NORMAL SPIN WASHER EXTRACTOR, LN-35 TP E

Made of stainless steel.
Capacity: 39 kg (1:9) or 35 kg (1:10).
Microprocessor "Touch Plus Control" with display.
26 pre-set programs (4 economic programs).
Possibility of programming, export and import programs through USB memory, without limite.
"WASH CONTROL" management software included.
Digital sequence display.
8 signals for automatic liquid dosing, programmable in time and delay.
Possibility to install an automatic detergent doser on the rear of the machine.
Detergent dispenser with 4 compartments (pre-wash, wash, bleachers and softeners).
Water levels completely modifiable.
3 water inlets (Hot water, Cold water, Soft water).
WET CLEANING SYSTEM:
-Water levels completely modifiable.
-Possible manual dosing for evey 8 signals during the cycle.
-Minimum washing speed: 15 r.p.m.
-Minimum thyrhm ON-OFF: 1 second.
Safety switch for door opening.
Wash and spin speeds are configurable.
These machines have electronic control of imbalance with frequency variator, that detects the load uncentered before spinning.
Hard mounted machine. Machine must be fixed to the floor. Elements not included.
Drum diameter: 860 mm.
Deepest drum: 602 mm.
Door diameter: 560 mm.
Spin speed: 455 r.p.m.
G Factor: 100.
Easy to attach automatic dosser dispenser at rear of machine.
Water consumption in program n° 2 60°: 400 litres.
Heating system: Electric.
Elements heating power: 21 kW.
Total power: 22,00 kW.
Dimensions: 979 x 1.066 x 1.408 mm

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	109	0	1.129		0
SOFT COLD WATER	506	0	1.322	3/4"	
DRAIN	347	0	143	3"	
COLD WATER	906	0	1.322	3/4"	
HOT WATER	586	0	1.322	3/4"	

