



Washer extractors

Normal Spin washer extractors TP

NORMAL SPIN WASHER EXTRACTOR, LN-60 TP E

DIMENSIONS		<u>Article</u>	Packed
Length	mm	1.225,00	1.360,00
Depth	mm	1.280,00	1.460,00
Height	mm	1.640,00	1.880,00
Weigth	Kg	930,00	1.050,00
Volumen	m3		3,73

ELECTRICITY

31,30 KW Electric power NO 230V -1+N

Opt: 3x25+T- 100 A 230V - III

4x10+T - 63 A 400V - III+N

WATER

650,00 Water consumption (lit/h) Pressure (Kg/cm2) 2 - 4

GAS

Not used

STEAM Not used

<u>AIR</u> Not used

LEVEL SOUND (dB) 60,00 NORMAL SPIN WASHER EXTRACTOR, LN-60 TP E

Made of stainless steel.

Capacity: 67 kg (1:9) or 60 kg (1:10).

Microprocessor "Touch Plus Control" with display.

26 pre-set programs (4 economic programs).

Possibility of programming, export and import programs through USB

memory, without limite.

"WASH CONTROL" management software included.

Digital sequence display.

 $\ensuremath{\mathbf{8}}$ signals for automatic liquid dosing, programmable in time and delay.

Possibility to install an automatic detergent doser on the rear of the machine. Detergent dispenser with 4 compartments (pre-wash, wash, bleachers and

softeners).

Water levels completely modifiable.

3 water inlets (Hot water, Cold water, Soft water).

WET CLEANING SYSTEM:

-Water levels completely modifiable.

-Possible manual dosing for evey 8 signals during the cycle.

-Minimum washing speed: 15 r.p.m.

-Minimum thythm ON-OF: 1 second.

Safety switch for door opening.

Wash and spin speeds are configurable.

These machines have electronic control of imbalance with frequency variator,

that detects the load uncentered before spinning.

Hard mounted machine. Machine must be fixed to the floor. Elements not

included.

Drum diameter: 1.048 mm. Deepth drum: 684 mm. Door diameter: 560 mm. Spin speed: 416 r.p.m. G Factor: 100.

Easy to attach automatic dosser dispenser at rear of machine.

Water consumption in program nº 2 60°: 650 litres.

Heating system: Electric.

Elements heating power: 28,8 kW.

Total power: 31,30 kW.

Dimensions: 1.225 x 1.280 x 1.640 mm

Connections points	Х	Υ	Z	Diameter	Information
ELECTRICITY	109	0	1.129		0
SOFT COLD WATER	750	0	1.322	3/4"	
DRAIN	545	0	410	3"	
COLD WATER	1.150	0	1.550	3/4"	
HOT WATER	830	0	1.322	3/4"	

