



Ironers & Flatwork Ironers

Ironers

IRONER, PE-25/100 M

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	1.400,00	1.480,00
Depth	mm	405,00	500,00
Height	mm	1.005,00	1.170,00
Weigth	Kg	110,00	120,00
Volumen	m3	0,57	0,85

ELECTRICITY

<u>Electric power</u>		<u>Article</u>	<u>Packed</u>
230V -1+N	KW		5,18
230V - III		3x2,5+T-20A	NO
400V - III+N		4x1,5+T-16A	

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) **55,00**

IRONER, PE-25/100 M

Outer casing of varnished steel, white colour.
 Roller coated in Polyester.
 Works by means of a pedal.
 Strap feeding.
 Return feed design requires minimum installation space.
 Safety protector for hands.
 Controlled by microprocessor.
 Temperature control by thermostat.
 Safety thermostat.
 Electric heating system.
 Roller diameter Ø 250 mm.
 Roller length: 1.000 mm.
 Speed: 4,20 m/minute.
 Production: 30 kg/h.
 Electrical connection: 400 V 3+N.
 Heating power: 5 kW.
 Electrical power: 5,18 kW.
 Dimensions: 1400 x 405 x 1005 mm.

Entry with 20% ÷ 25% maximum humidity

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	80	0	765		0

