



Ironers & Flatwork Ironers

Compact flatwork ironers, Poseidon series

COMPACT FLATWORK IRONER, PSE-60/260 PL

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	3.745,00	3.900,00
Depth	mm	1.475,00	1.600,00
Height	mm	2.020,00	2.100,00
Weigth	Kg	2.400,00	2.450,00
Volumen	m3	11,16	13,10
<u>ELECTRICITY</u>			
<u>Electric power</u>		KW	61,90
230V - I+N			NO
230V - III			NO
400V - III+N		4x35+T - 125 A	
<u>WATER</u>			
Not used			
<u>GAS</u>			
Not used			
<u>STEAM</u>			
		Not used	
<u>AIR</u>			
Consumption		NI/min	9.000,00
Pressure		kg/cm2	7
<u>LEVEL SOUND</u>			
		(dB)	60,00

COMPACT FLATWORK IRONER, POSEIDON SERIES, PSE-60/260 PL

Roller: Ø 600 mm - Length: 2.600 mm.

Production: 75 ÷ 105 kg/h.

Poseidon series includes a lengthwise folder to make a maximum of two longitudinal pleats.

It works on 1 or 2 independent lanes.

Linen outlet in the front part of the machine, optional rear outlet.

Outer casing made of white-lacquered steel.

Control through a microprocessor (PLC).

Steel-coated roll.

NOMEX - POLYESTER feeding straps.

Special NOMEX ironing straps.

Adjustable ironing speed between: 3 ÷ 18 m/min.

Safety protector for the hands.

Electronic thermostat and probe to adjust the temperature.

Extraction system: 2 x 1000 m3/h.

Compressed air (necessary): 7 bar.

Compressed air consumption : 9.000 NI/h.

Electric heating system.

Heating power: 60 kW.

Maximum electrical power: 61,90 kW.

Dimensions: 3.745 x 1.475 x 2.020 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	245	0	170		
AIR	180	0	170	12 mm	
EXHAUST	365	165	1.900	120 mm	
EXHAUST	3.575	165	1.800	120 mm	

