



Ironers & Flatwork Ironers

Compact flatwork ironers, Polaris series

COMPACT FLATWORK IRONER, PSE-60/330

<u>DIMENSIONS</u>		Article	Packed
Length	mm	4.390,00	4.500,00
Depth	mm	1.475,00	1.600,00
Height	mm	2.020,00	2.100,00
Weigth	Kg	2.850,00	2.900,00
Volumen	m3	13,08	15,12
<u>ELECTRICITY</u>			
<u>Electric power</u>		KW	61,90
230V -1+N			NO
230V - III			NO
400V - III+N		4x35+T - 125 A	
<u>WATER</u>			
Not used			
<u>GAS</u>			
Not used			
<u>STEAM</u>		Not used	
<u>AIR</u>			
Consumption	NI/min		9.000,00
Pressure	kg/cm2		7
<u>LEVEL SOUND</u>		(dB)	60,00

COMPACT FLATWORK IRONER, POLARIS SERIES, PSE-60/330

Roller: Ø 600 mm - Length: 3.300 mm.
 Production: 110 ÷ 140 kg/h.
 It works on 1 or 2 independent lanes.
 Linen outlet in the front part of the machine, optional rear outlet.
 Outer casing made of white-lacquered steel.
 Control through a microprocessor (PLC).
 Steel-coated roll.
 NOMEX - POLYESTER feeding straps.
 Special NOMEX ironing straps.
 Adjustable ironing speed between: 3 ÷ 18 m/min.
 Safety protector for the hands.
 Electronic thermostat and probe to adjust the temperature.
 Extraction system: 2 x 1000 m3/h.
 Compressed air (necessary): 7 bar.
 Compressed air consumption : 9.000 NI/h.
 Electric heating system.
 Heating power: 60 kW.
 Maximum electrical power: 61,90 kW.
 Dimensions: 4.390x 1.475 x 2.020 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	380	0	170		
AIR	330	0	170	12 mm	
EXHAUST	290	165	1.800	120 mm	
EXHAUST	4.220	165	1.800	120 mm	

